#### ACCESSORIES













Via 2 Giugno, 19 • 40011 Anzola Emilia (Bo) • Italia Tel. +39 051 731051 • Fax +39 051 731925 E-mail: orteco@orteco.com • Internet: www.orteco.com





Pile driver ORTECO
SMART on crawler is
designed and made to
perform the work of
fixing the posts
at the best.

The adopted light weight and the technical solutions aim at reducing costs and, lowering consumption and noise, to protect the environment.

# "I ECNOLOGIA DE POTENZA DE la portata di mano"





# PILE DRIVER ON CRAWLER SMART 600 800



#### **BACK** VIEW

Oil-pressure pipes are well positioned behind the main frame for safety purposes in case oil under pressure came out.



#### **SOUND-PROOF** ENGINE

The ORTECO pile drivers are equipped with sound-proof engines of excellent quality which comply with the most severe European standards for air pollution (antiparticle silencers assembled upon request).





### **CONTROLS**

The ORTECO pile driver on crawler of the SMART line has been especially designed to guarantee operator's safety and ergonomics.

In fact, translation controls are well separated from pile driver's controls.



## **TRANSPORTATION**


ORTECO pile drivers can be easily loaded inside truck bodies thanks to reduced dimensions in transportation position.



#### TECHNICAL DATA

| MODEL:   |                 | 600SC     | 800SC     |
|--|-----------------|-----------|-----------|
| Hammer rating  | joule           | 600       | 830       |
| Blows per minute   | n.              | 650/1000  | 680/720   |
| Inclination kit  |                 | standard  | standard  |
| Extractor connection   |                 | standard  | standard  |
| Auxiliary plant for accessories  |                 | standard  | standard  |
| Hatz Diesel engine   |                 | 2L41C     | 2L41C     |
| Electric starting  | volt            | 12        | 12        |
| Noise level  | dbA             | 112       | 112       |
| Horse power (at 3000 RPM)  | Kw (CV)         | 21,3 (29) | 21,3 (29) |
| Max pressure   | Мра             | 15        | 15        |
| Oil flow   | dm³/min         | 75        | 75        |
| Oil tank capacity  | dm <sup>3</sup> | 110       | 110       |
| Diesel oil tank capacity   | dm <sup>3</sup> | 50        | 50        |
| Total weight   | kg              | 2850      | 3000      |
| Manufacturer reserves the right to change the technical features above mentioned without prior notice. |                 |           |           |

right to change the technical features above m Pictures may show not standard accessories.







#### **VERTICALITY**

The vertical column may be hydraulically positioned to obtain excellent uphill or downhill pile driving.